

## DANISH OIL

**Dulux Trade** Danish Oil is a blend of natural oils that permeate the wood surface to provide a natural water-resistant finish as well as enhancing the natural beauty of the wood. It can be used on all wooden interior and exterior surfaces including furniture, doors, and wood decorations. **Dulux Trade** Danish Oil is a clear coat that provides a beautiful matt finish.

### KEY BENEFITS

- Nourishes & Protects
- All Types of Wood Surfaces
- Solvent-Based

### PRODUCT INFORMATION

#### Typical Use

Suitable for hardwoods and softwoods.

#### Pack Size

1L and 2.5L.

#### Colour Range

Clear oil.

#### Composition (nominal)

**Pigment:** N/A.

**Binder:** High performance resin.

**Solvent:** White spirit.

#### Volume Solids

50% (nominal).

### SURFACE PREPARATION

To get the best results, ensure new, bare wood is clean and dry before treatment. Previously treated wood should be sanded to provide the best

finish. Waxes should be removed with white spirit. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### SYSTEMS INFORMATION

If treating bare wood apply 3 coats of Dulux Trade Danish Oil, allowing a minimum of 6 hours between coats.

### APPLICATION METHOD

Brush and cloth only.

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 6m<sup>2</sup> coverage per litre. The figure will vary depending on the porosity of the wood.

#### Thinning

Do not thin this product.

## DANISH OIL

### Spray Recommendations

For health and safety reasons related to all solvent-based paints, spray application is not recommended.

### Drying Times

*Single coat at standard thickness:*

**Touch Dry:** 4-6 hours.

**Recoat:** 16 hours.

### Cleaning Up

After use, remove as much product as possible from brushes before cleaning with brush cleaner.

Take extra care when disposing of items such as cleaning rags and paper wipes as there is a risk of self-ignition. Contaminated materials should be soaked in warm, soapy water and placed in a closed metal container before disposal.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp).

### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.: A/e): 400g/l (2010). This product contains max. 399g/l VOC.  
VOC content: High (25-50%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:0333 222 70 70).

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet (SDS 620) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)