

# ASTARI DESMOLACK A&B®

Polyurethane Primer for Wooden Floors



## DESCRIPTION

**ASTARI DESMOLACK A&B** is a clear, two-component polyurethane primer for wooden floors. It provides an ideal undercoat for VIVECHROM's floor varnish DESMOLACK D&F. It exhibits strong adhesion, dries fast and can be rubbed down easily.

## PRODUCT INFORMATION

**Type:** Two-component PU floor primer  
**Mixing ratio:** A/B = 2/1  
**Specific gravity:** 1.02 ± 0.01 gr/cm<sup>3</sup> (ISO 2811)  
**Application method:** Roller or Brush  
**Pot life:** 2 hours at 25° C  
**Spreading Rates:** About 9m<sup>2</sup> per litre on previously prepared surfaces  
**Thinning:** Ready for use  
**Drying times:** Touch dry in 1 hour and recoatable after 2 hours.  
 Drying time depends on weather conditions (humidity, temperature)  
**Storage:** Store between 5° to 40° C.

Strong adhesion

Dries Fast

## SURFACE PREPARATION

- Sand the floor with a sanding machine or abrasive paper No 80-150.
- Remove dust thoroughly.
- Cleaning of the floor with water should be avoided because it affects adversely the finishing coat.
- Treatments such as dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. Work in well ventilated areas. Use suitable personal protection equipment.

### VOC (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product (category A/j): 500 g/l (2010).  
 This product (A+B mix) contains max 499 g/l VOC.





# ASTARI DESMOLACK A&B®

Polyurethane Primer for Wooden Floors

## APPLICATION

- Mix components A & B with a ratio 2 to 1.
- Stir very well until the mixture is homogenized and then apply the first coat.
- After a 2 to 4 hours interval, you can apply DESMOLACK D&F floor varnish with no need to rub the surface.
- In cases where more than 4 hours pass then it is vital to rub down thoroughly with abrasive paper No 180 and after that you can apply the floor varnish.

## AFTER USE – WASTE MANAGEMENT

Remove as much paint as possible from brushes and rollers before cleaning • Clean brushes and equipment with VIVECHROM's ACETON immediately after use.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

### Desmolack A

**DANGER.** Contains n-butyl acetate • Highly flammable liquid and vapour • Causes serious eye irritation • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Do not get in eyes, on skin, or on clothing • Wear protective gloves • Wear eye or face protection • Call a POISON CENTER or doctor if you feel unwell • Keep cool • Repeated exposure may cause skin dryness or cracking • Do not empty into drains • Dispose of contents and container in accordance with all local regulations. Poison Center Tel. +302107793777



**Desmolack B**

DANGER. Contains Toluene diisocyanate • Highly flammable liquid and vapour • Harmful if inhaled • Causes serious eye irritation • Causes skin irritation • May cause allergy or asthma symptoms or breathing difficulties if inhaled • May cause an allergic skin reaction • May cause drowsiness or dizziness • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Keep away from heat, sparks, open flames and hot surfaces • No smoking • Do not get in eyes, on skin, or on clothing • Wear protective gloves • Wear eye or face protection • IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call the POISON CENTER or a doctor • Keep cool • Repeated exposure may cause skin dryness or cracking • Do not empty into drains • Dispose of contents and container in accordance with all local regulations • Contains isocyanates. May produce an allergic reaction.

Poison Center Tel. +302107793777



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**

