

# RADIATER AQUA ECO

Special Waterborne Paint for Radiators



## DESCRIPTION

RADIATER AQUA ECO is a special waterborne paint for radiators with special state of the art raw materials. It is certified and fulfills the criteria of the European Union Eco-Label Board. It exhibits high temperature durability and excellent gloss and whiteness retention for a long time. It has great adhesion and coverage and is suitable for recoating old solvent-based trims. It has great elasticity and hardness and is scratch & knock resistant. It has excellent working and leveling properties, it dries fast and it doesn't smell.

## PRODUCT INFORMATION

**Type:** Special Waterborne Paint for Radiators

**Application method:** Brush, roller or spray gun.

**Thinning:** With clean water 5-10% for brush or roller, 20-30% for spray gun.

**Spreading rates:** About 12 m<sup>2</sup> per litre per coat on previously prepared surfaces.

**Drying times:** Touch dry after 1 hour and recoatable after 6 hours. Drying time depends on weather conditions (humidity, temperature).

**Colours:** It is available in white, in gloss and satin finish.

**Storage:** Store between 5°C to 40°C. If you do not use the whole quantity, close carefully the lid for next use.

### VOC (Volatile Organic Compounds)

EU limit value for this product category A/d Interior/exterior trim and cladding paints for wood and metal: 150 g/l (2007) and 130 g/l (2010). This product contains max 60 g/l VOC.

**High temperature durability**

**Quick dry**

**Low odor**





# RADIATER AQUA ECO

## Special Waterborne Paint for Radiators

### SURFACE PREPARATION

- Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and rust.
- On new surfaces or on metal surfaces with peeled-off old paint, apply RUST PRIMER by Vivechrom.
- When repainting radiators, thoroughly rub down previous coat, using a suitable abrasive paper.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

### APPLICATION

- Thin with clean water 5-10% for brush or roller, 20-30% for spray gun and stir well before use. Apply 2 coats of RADIATER AQUA ECO with total consumption per coat 100ml/m<sup>2</sup>.
- Apply the paint and let it dry at temperatures between 10°C to 35°C.
- High temperature durability up to 80°C water temperature

### AFTER USE – WASTE MANAGEMENT

- Remove as much paint as possible from brushes and rollers before cleaning
- Clean brushes and equipment with water and detergent solution after use
- Do not put residual paint down the kitchen sink or toilet, or into a waste bin
- Unused paint requires specialist handling for safe environmental disposal and that it should not therefore be thrown away with household refuse
- Advice regarding disposal and collection should be sought from the local authority
- Recover unused paint for re-use
- Reuse of paint can effectively minimize the products' life cycle environmental impact.


### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing • Call a POISON CENTER or doctor if you feel unwell • Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction • Close well after application. Store in a cool place • Dispose of contents and container in accordance with all national regulations.

Emergency Tel. Number of Official Advisory Body: +30210 7793777



**STIR WELL BEFORE USE - PROTECT FROM FROST  
DO NOT APPLY AT TEMPERATURES UNDER 10°C.**



[www.vivechrom.gr](http://www.vivechrom.gr)